

Lockable Payment Terminal Stand Setup Sheet

For Part Numbers starting with MMF-PSL## or MMF-PS##



Assembly Instructions

STEP 1

Firmly secure stand by bolting (3) screws through the round base plate to a flat counter surface. (NOTE: Screws are not included as they need to suit your specific desktop or platform thickness).

STEP 2

Mount payment terminal to stand by sliding in place and/or align the three (3) stand-offs on the stand's mounting plate to the three holes on the bottom of the terminal. NOTE: Some stands as the MMFPS1104 shown on the right, only require to slide the terminal into the cradle and do not have stand-offs.



Image of P/N: MMFPS1104

STEP 3

Make the necessary cable connections to the terminal; secure and route cables as needed using space allotted between the mounting plate and pole.

STEP 4

Place the Stop-Bracket and tighten the two button head cap screws behind the mounting plate using the 5/64" hex wrench provided in the kit. If part number format is as follows: MMF-PS##, go to STEP 6

STEP 5 (Applies to units with part numbers starting with MMF-PSL##)

Place the locking cover over the Stop-Bracket by inserting right-side tab of the cover into the slot provided on the mounting plate. Turn key counter clockwise to lock.

STEP 6

Adjust tilt as desired by tightening the side knob on the right side of the mounting plate.

NOTE: P/N: MMFPS1104 is factory set to a specific tension, refer to STEP 7 for Tension Adjustment on that model.

STEP 7 (Optional) Tension Adjustment for MMFPS1104

Tools needed: 5/32 Allen Wrench (provided) and a 7/16 Box Wrench (not included)

1. Open plastic cover screw caps on each side.
2. Loosen inside jam nut with 7/16 box wrench.
3. Firmly hold the 5/32 Allen Wrench on the Button Head Screw and turn to desired friction. (To tighten: Clockwise / To loosen: Counter-clockwise)
4. While applying pressure on the button head screw with the Allen Wrench, turn the inside nut with the Box Wrench to lock in place.

TOOLS AND HARDWARE REQUIRED

- One (1) 5/64" hex wrench and two (2) #6-32 button socket head cap screws are included in the kit to tighten the L-Bracket
- No hardware is included for surface mounting since hardware will need to suit your specific desktop or platform thickness.
- Phillips head screw driver or power drill will be required to mount stand to desired surface (if necessary).

PRODUCT SPECIFICATIONS

Rotation:	180° left to right
Tilt:	up to 30° upright adjustable angle
Pole inside diameter:	1.87"
Pole height:	2" high
Base outer diameter:	4"
Construction:	Steel
Finish:	Textured Powder Coat
Lock:	2 Positions – Keyed Alike (two keys included)
Color:	Black
Cable Management Area:	Yes

For parts or additional accessories, contact your supplier or visit www.mmfps.com